



ABSPMS-60L - 60 Quart Heavy Duty Electronic Planetary Mixer



MARKETING SPECIFICATION

Specified mixer shall be an ABSPMS-60L, 60 Quart Capacity Planetary Mixer with Solid Welded Steel Body Finished in NSF epoxy Paint and fitted with four Non-Skid Foot Pads for stability. Mixer shall be equipped with Stainless Steel Bowl, Whip, Hook, Pour Spout and Aluminum Paddle. Mixing Tools shall be fitted closely to the bottom and sides of the mixing bowl to eliminate hand scraping. Mixer shall be equipped with a Ten-Speed Digital Control Panel-Featuring 'Shift on the Fly'-No Stopping between speed Changes, Slow Start Up on all Speeds, and Manual or Timed Mixing. Mixer shall be equipped with a Non-Slip, Low Noise, High Torque Drive System, Safety Interlocked Full Bowl Cover with ingredient opening for Pour Spout, and Emergency Stop mounted at eye level. Mixer shall have Power Bowl Lift as Standard Equipment. Mixer shall be ETL Listed and Comply with UL 763 and NSF 8 Standards.

Model ABSPMS-60L

36 lbs flour / 57.6 lbs dough capacity

STANDARD FEATURES

- Strong Welded Steel Body with NSF epoxy paint
- Stainless Steel Bowl, Whip, Hook, Pour Spout and Aluminum Paddle
- Digital Control Panel- 10 Speeds- 'Shift on the Fly'- without stopping
- Digital Timed or Untimed Operation
- Heavy Duty 4.0 HP Motor -- 208-220/60/3
- High Torque, Dual Stage non-Slip Quiet Belt Drive.
- Heavy Duty Hinged Bowl Cage with Safety Interlock
- Cushioned Feet for enhanced stability
- No Gears to Break, No Oil to Leak and no Seals to Fail
- Power Bowl Lift

CONTROL AND PERFORMANCE FEATURES

- Digital Control- 10 Speeds - Timed or Untimed Operation
- High Torque, Dual Stage, Non-Slip, Silent Belt Drive
- Automatic Over-Current Protection with External Reset
- Emergency Stop mounted at EYE Level
- Standard Attachments - Stainless Steel Hook, Whip, Pour
- Spout and Aluminum Paddle
- 6 Foot Electrical Cord with NEMA Cord Cap

OPTIONS & ACCESSORIES

- ABSPMS-60/30L: 30-Quart Bowl, Hook, Paddle, Wire Whip Included; No Adapters Necessary

STANDARD PRODUCT WARRANTY

- One-Year Parts and Labor on defective parts (Contiguous US and Canada Mainland)



Meets UL 763 and NSF-8

AMERICAN BAKING SYSTEMS, INC. 290 LEGION COURT S.W.

CEDAR RAPIDS, IA 52404 Phone:

319-373-5006 Fax: 319-373-5008


Email: INFO@ABS1.NET WEB: www.abs1.net





60-Quart Heavy Duty Electronic Planetary Mixer

ABSPMS-60L



MODEL ABSPMS-60L UTILITY SPECIFICATIONS	
Electrical	208-240/60/3
Plug	NEMA 5-15P
Breaker	Breaker - Type B RCD or RCM
Motor HP	4.0 HP
Agitator Speed (RPM)	Low: 165 High: 450
Motor kW	3

ABSPMS-60L CAPACITIES		
Capacity (lbs)	Flour	36
Dough	57.6	

SHIPPING							
Model	Crated Dimensions Height x Width x Depth	Unit Dimensions Height x Width x Depth	Weight	Net Weight	Freight Class	Door Clearance	Fork Lift Delivery Recommended
ABSPMS-60L	65" x 35" x 48"	59 x 33 x 43	1100	890	85	36" or wider	Yes